

## Parkway 3



- [Print Specifications](#)

Dimensions: [US](#) | [METRIC](#)

### Power

<b>Engine</b>	Kubota V1505, Vertical, water-cooled, 4-cycle diesel engine
<b>Displacement</b>	1498 cc
<b>Starting System</b>	12 V electric start
<b>Power</b>	25 kW @ 3000 rpm
<b>Fuel Capacity</b>	51 litres

### Drive Train

<b>Traction Drive</b>	On-demand cross-flow 4 wheel drive system, 2 wheel drive in transport mode. Direct coupled variable displacement pump.
<b>Cutting Unit Drive</b>	Fixed displacement hydraulic motors
<b>Hydraulic Tank Capacity</b>	42 liters
<b>Grade of Hydraulic Oil</b>	ISO 46 Oil

### Speed (Maximum)

<b>Cutting</b>	12 km/h
<b>Transport</b>	25 km/h

---

## Brakes

<b>Service</b>	Positive hydrostatic braking
<b>Parking</b>	Fail safe, zero maintenance, oil immersed wet disc brakes

---

## Tyres

<b>Front</b>	26 x 12 - 12 8pr
<b>Rear</b>	20 x 10.00 - 8 4pr

---

## Steering

Hydrostatic powered steering to rear wheels

---

## Controls

Starter key switch, throttle control lever, parking brake, cutting unit switch, individual cutting unit lift/lower control, weight transfer switch, traction pedal, steering tilt control, horn, auto diff lock, hazard warning switch, lighting kit switches (where fitted), optional rotating beacon, TST™ (Tilt Safety Technology) option

---

## Dimensions

<b>Length</b>	2.67 m
<b>Transport Width</b>	1.60 m
<b>Height</b>	1.50 m ROPS folded
<b>Weight</b>	1355 kg (with ROPS, 6 knives MAGNA & full fuel)
<b>Wheel Base</b>	1.50 m
<b>Wheel Track</b>	1.3 m front / 1.1 m rear

---

## Cutting

<b>Type</b>	Three hydraulically driven 762 mm w.o.c. cylinders
<b>Weight Transfer</b>	Units balanced with hydraulic weight transfer

---

<b>Cutting Unit Lift</b>	Individual hydraulic lift/lower to units
<b>Cutting Cylinder</b>	Magna 250 6 Knife, 254 mm diameter, fixed head Sport 200 8 Knife, 197 mm diameter, floating head
<b>Width of Cut</b>	2.15 m
<b>Height of Cut</b>	Fixed Head - Magna 250: 12.7 - 61 mm  Floating Head - Sport 200 Standard blade: 12.7 - 35.7 mm  Floating Head - Sport 200 Thin blade: 9 - 32 mm
<b>Cutting Performance (area)</b>	2.3 ha/h at 12 km/h with 6 knife fixed head units 2.3 ha/h at 12 km/h with 8 knife floating head units

---

## Rollers

<b>Front</b>	Sport 200: Full width 76 mm diameter grooved roll
<b>Rear</b>	Magna 250 & Sport 200: Full width 76 mm diameter solid roll
<b>Cylinder Adjustment</b>	Tool or hand wheel

---

## Operator Ear Noise Levels (Sound Pressure)

85.3 dB (A) Leq (98/37/EC)

---

## Measured Sound Level

101 dB(A) LWA

---

## Hand/arm vibration levels

0.39 m/s<sup>2</sup>

---

## Optional Equipment

Lighting kit, rotating beacon, Grammer air suspension seat, deluxe cab with heater and air conditioning, puncture resistant tyres, spanner adjustment height of cut

