

# AR530

## ARTICULATED CONTOUR ROTARY MOWER



- **TRUEDECK™ HEAVY-DUTY CONTOURING**
- **SUPERIOR AFTER-CUT APPEARANCE**
- **QUICK AND EASY DECK ADJUSTMENT**
- **TRUSTWORTHY KUBOTA® ENGINE**

Redesigned from the ground up, the AR530 contour rotary mower is built to give you the best.

Designed with TRUEDECK™ heavy-duty contouring decks, with best in class clippings distribution and superior after-cut quality, it climbs hills and contours smoothly, eliminating the risk of scalping.

The AR530 offers quick and easy deck adjustments and a trustworthy Kubota® engine you can rely on.

CUT WIDTH  
**90"**  
(2.3M)

CUT HEIGHT  
**0.75" - 4.5"**  
(19MM - 114MM)  
0.25" (6MM)  
INCREMENTS

FUEL CAPACITY  
**17 GAL**  
(64.2L)

MOWER ENGINE  
**KUBOTA®**  
**50.2HP**  
(37.4KW) DIESEL



SINCERELY

*Jake*

For information and support:  
[www.jacobsen.com](http://www.jacobsen.com) / +44 (0) 1473 270 000



Engine horsepower may vary due to conditions of specific use. Product available in selected countries.  
NOTE: Specifications, while correct at time of printing, may change without notice.  
© 2024 Textron Specialized Vehicles Inc. 10024-G2 (Rev. 06/2024)

# AR530

## ARTICULATED CONTOUR ROTARY MOWER



Full color LCD operator screen with machine diagnostics

Premium air ride suspension seat on every unit - work all day in comfort.

Foldable ROPS

Improved operator environment; ease of access, optimized seating position, adjustable steering wheel

Hydraulic hood struts for worry free access and convenience

Programmable performance setting allows you to be in control of transport, mow and turn speeds

Reversing fan as standard

Maintenance-free, wet parking brakes

Jake's best traction that meets your application

90" (2.3m) cutting width

Decks specifically designed for cut performance and after-cut appearance



Vertical lift on outside decks for maneuverability



50.2 HP (37.4 kW) diesel Kubota® engine



TRUEDECK™ heavy-duty cutting decks

### DECKS & CUTTING UNITS

NUMBER AND SIZE	5 x TRUEDECK™ 23" (58.4cm) rotary cutting units. Equipped for rear-discharge chute and smooth rear roller. Mulching baffle, non-stripping rear roller and rear roller scrapers available
BLADE MATERIAL	5 x 22.4" (56.8cm) heat treated alloy combo blades
DECK LIFT & LOWER	Hand operated, joystick controlled hydraulic lift system
WEIGHT TRANSFER	Adjustable hydraulic weight transfer – automatic electronic activation at operator controls with mow switch. Selectable through control console
DECK CONSTRUCTION	Heavy duty modular deck construction

### TRACTION, BRAKES & SPEED

TRACTION DRIVE	SureTrac II™ AWD, a unique parallel hydrostatic system, servo-controlled variable displacement hydro; four high-torque wheel motors; 2WD transport and reverse
DECK DRIVE	Fixed displacement, self-lubricating with 1" (2.54cm) diameter shaft; double sealed bearings
HYDRAULIC SYSTEM	10 gal. (37.9L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter, 40 gpm. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic through traction system
PARKING BRAKES	No-Maintenance, Integrated Wet Parking Brake
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	5.5mph (8.8kph)
TRANSPORT SPEED	9.3mph (15kph)

### WEIGHTS & DIMENSIONS

WEIGHT	3451lb. (1565kg) full fluids
LENGTH	137.5" (3.49m)
OVERALL HEIGHT (ROPS UP)	91.6" (232.6cm)
WHEELBASE	63" (1.6m)
TRANSPORT WIDTH	88.6" (2.25m)
WORKING WIDTH	95.3" (2.42m)

### WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

### ACCESSORIES

- 692771 Blade 23.14 Hi-lift
- 692774 Blade 23.14 combo
- 692775 Blade 23.14 mulch
- 68127 Canopy kit
- 677080 Kit - quick release pin, 5 gang
- 677092 Kit - mulching, 23"
- 677261 Kit - quick release pin, 7 gang
- 689563 Kit - 23" cable scraper
- 698270 Roller - service 76 x 567 grooved polymer
- 698272 Roller - service 76 x 567 solid polymer
- 4394939 Acc, cargo net
- 10002064 Kit - 23" grooved roller scraper