

AR730

LARGE, ARTICULATED CONTOUR
ROTARY MOWER

WIDTH AND EFFICIENCY AT YOUR FINGERTIPS

This highly efficient rotary mower can handle any terrain it's faced with. The AR730 can offer 5 or 7 cutting decks thanks to the innovative TrueDeck construction, ensuring it excels in clip dispersal and after-cut appearance. With its ability to cover up to 4.5 acres in an hour at a speed of 5.5 mph, and a cutting width of 124" it gives you the confidence that it will perform with limited maintenance.



BREAK-BACK WING DECK
PROTECTION SYSTEM

7 TRUEDECK™ CONTOUR ROTARY
DECKS FOR EXTENSIVE COVERAGE

INCOMMAND II CONTROL SYSTEM

CUT WIDTH

124"
(3.15M)

CUT HEIGHT

**0.75"-
4.5"**
(19MM - 114MM)

CUTTING CAPACITY

UP TO **8.7** ACRES AT
7 MPH
(3.52 HA/HR AT 11.27 KPH)

FUEL CAPACITY

17 GAL
(64.2L)

MOWER ENGINE

65.2HP
(48.6 KW) DIESEL



JACOBSEN

Actual operating power output may vary due to conditions of specific use.
Run time will vary based on conditions of specific use, accessories, and terrain.
NOTE: Specifications, while correct at time of printing, may change without notice.
© 2025 Textron Specialized Vehicles Inc. 10042-G1-INT (Rev. 01/2025)

AR730

LARGE, ARTICULATED CONTOUR ROTARY MOWER



Make adjustments efficiently, allowing for increased mowing time and a height of cut that suits you.



The AR730's SureTrac II™ AWD system allows the mower to navigate complex and demanding terrains with ease.



The trustworthy 65.2HP Kubota engine is both durable and dependable, making it more than capable of consistent cutting.



DECKS & CUTTING UNITS

NUMBER AND SIZE	7 x TRUEDECK™ 23" (58.4 cm) rotary cutting units. Equipped for rear-discharge chute and smooth rear roller. Mulching baffle, non-stripping rear roller and rear roller scrapers available.
BLADE MATERIAL	7 x 22.4" (56.8 cm) heat treated alloy combo blades
DECK LIFT & LOWER	Hand operated, joystick controlled hydraulic lift system. Wing decks can be deactivated and lifted independently.
WEIGHT TRANSFER	Adjustable hydraulic weight transfer – automatic electronic activation at operator controls with mow switch. Selectable through control console
DECK CONSTRUCTION	Heavy-Duty Modular Deck Construction
TRACTION, BRAKES & SPEED	
TRACTION DRIVE	SureTrac II™ AWD, a unique parallel hydrostatic system, servo-controlled variable displacement hydro; four high-torque wheel motors; 2WD transport and reverse
DECK DRIVE	Fixed displacement, self-lubricating with 1" (2.54 cm) diameter shaft; double sealed bearings
HYDRAULIC SYSTEM	10 gal. (37.9 L) capacity; hydraulic tank oil level monitor and horn alarm; GreensCare biodegradable fluid; full-flow, 10-micron filter, 40 gpm. Side-by-side radiator/hydraulic oil cooler.
SERVICE BRAKES	Dynamic through traction system
PARKING BRAKES	No-Maintenance, Integrated Wet Parking Brake
STEERING	Rear wheel, hydrostatic power steering with tilt adjustable steering wheel
MOWING SPEED	5.5 mph (8.8 kph)
TRANSPORT SPEED	5 mph (8 kph)
WEIGHTS & DIMENSIONS	
WEIGHT	4235 lbs. (1921 kg) full fluids
LENGTH	137.5" (3.49 m)
OVERALL HEIGHT (ROPS UP)	91.6" (232.6 cm)
WHEELBASE	63" (1.6 m)
TRANSPORT	88.6" (2.25m)
WORKING WIDTH	133" (3.38 m)
WARRANTY	
MOWER WARRANTY	2 Years

JACOBSEN

For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946

