

TR330

HIGH TRACTION SIDE SHIFTING TRIM MOWER



- **ADAPTISHIFT™ SIDE SHIFTS REELS AT YOUR COMMAND**
- **TRUSTWORTHY KUBOTA ENGINE**
- **ZERO MAINTENANCE WET PARKING BRAKES**
- **3WD TRACTION SYSTEM**

The TR330 high traction, side shifting trim mower is always consistent and dependable, with ADAPTISHIFT™ Reels at your command.

The TR330 is fitted with a trustworthy clean, green engine and has the narrowest width for easy transport and storage. This mower brings together comfort, manoeuvrability, cut quality and power, to make sure you can safely reach every blade of grass.

CUT WIDTH 72" (1.83M) OR 84" (2.13M) <small>featuring ADAPTISHIFT™ with up to 12" (30.5cm) of offset</small>	CUT HEIGHT 0.37" - 2.75" <small>(9.5MM - 69.8MM)</small>	CUTTING CAPACITY 4.5 - 5.3 AC <small>(1.83 - 2.13HA) / HR</small> <small>(1.83 - 2.13M X 10KM / HR)</small>
FUEL CAPACITY 7.6 GAL (28.7L)	MOWER ENGINE KUBOTA® 24.8HP (18.6KW) DIESEL	BLADES PER REEL 5, 7 OR 11



SINCERELY

Take

For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946



Actual operating power output may vary due to conditions of specific use. Run time will vary based on conditions of specific use, accessories, and terrain. NOTE: Specifications, while correct at time of printing, may change without notice.

© 2021 Textron Specialized Vehicles Inc.

TR330

HIGH TRACTION SIDE SHIFTING TRIM MOWER



Fully adjustable control arm with LCD screen and fingertip controls

Tilt steering wheel

Jake's Signature 26" (0.66m) or 30" (0.76m) reels

ROPS as Standard

Easy access engine service bay

Available in 3WD & 4WD

Service-free wet parking brakes



Adaptishift™ side shifts reels at your command



Trustworthy, powerful engine



Contour following articulated reels

REELS & BLADES

NUMBER AND SIZE	3 x 26" (0.66m) or 30" (0.76m) reels; 7" (178mm) diameter
BLADE MATERIAL	Hardened, high manganese carbon steel
CUTTING UNIT LIFT	Armrest mounted joystick
CUTTING FREQUENCY	-

TRACTION, BRAKES & SPEED

TRACTION DRIVE	Parallel-series "on demand" 3WD
REEL DRIVE	Fixed displacement hydraulic
HYDRAULIC SYSTEM	8.7 gal. (33L) capacity, full flow filtration (10 micron filter); GreensCare biodegradable oil
SERVICE BRAKES	Dynamic braking through hydrostatic drive
PARKING BRAKES	Service-free electronic wet disc
STEERING	Hydraulic power steering with tilt wheel
MOWING SPEED	6.2mph (10km/h)
TRANSPORT SPEED	8.7mph (14km/h)

WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	1664 - 2299lb (755 - 1043kg)
LENGTH	97" (2.46m)
OVERALL HEIGHT (including ROPS)	80" (2.04m)
WHEELBASE	43.5" (1.36m)
TRANSPORT WIDTH	83" (2.11m)
WORKING WIDTH	83" (2.11m)

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- Slick tires
- Light kit
- Canopy
- Verticuting reels
- Backlap kit
- Weight transfer kit
- Grass baskets