

F305

POWERFUL WIDE AREA REEL MOWER



- **RELIABLE & PRODUCTIVE WITH A SUPERIOR FINISH**
- **DURABLE CUTTING UNITS FOR TOUGHEST CONDITIONS**
- **POWERFUL KUBOTA ENGINE**

The F305 is a medium weight, four wheel drive, 5 unit fairway mower. This model gives reliable and unsurpassed productivity synonymous with the Jacobsen range. The F305 now benefits from revolutionized operator controls and a powerful yet clean Stage V 44HP Engine.

Four wheel drive comes as standard allowing for greater traction and a light touch on fine sports turf. Deluxe adjustable highback suspension seat gives increased operator comfort. The 26" (66cm) cutting units require no tools to adjust reels and can easily be set to discharge grass to the rear.

CUT WIDTH
116"
(2.94M)

CUTTING CAPACITY
10.67 AC
(4.32HA) / HR
AT 7.5MPH (12KM/H)

CUT HEIGHT
0.47" - 1.85"
(12MM - 47MM)

FUEL CAPACITY
9.98 GAL
(45.4L)

DRIVE SYSTEM
HYDROSTATIC - SERVO CONTROLLED

MOWER ENGINE
KUBOTA® 44.3HP
(33KW) DIESEL



SINCERELY

Take

For information and support:
www.jacobsen.com / +44 (0) 1473 270 000 / +1-888-438-3946



Actual operating power output may vary due to conditions of specific use. Run time will vary based on conditions of specific use, accessories, and terrain. NOTE: Specifications, while correct at time of printing, may change without notice.

© 2021 Textron Specialized Vehicles Inc.

F305

POWERFUL WIDE AREA REEL MOWER



Mechanical suspension seat with arm rests

Advanced operator platform and controls

Pedal with adaptable mow and transport speed

Adjustable steering column

Heavy-duty 26" (66cm) Jake Signature cutting units for a wide variety of conditions

ROPS as standard

Easy-access hood

Clean, Stage V engine technology

SureTrac™ 4WD traction System



Clear on board engine and service diagnostics



Removable engine bay side panels



Wide stance rear axle for excellent stability and aftercut appearance

REELS AND BLADES

CUTTING UNITS	26" (66.4cm) cylinder, 6.5" (16.5cm) diameter floating head cutting unit (5 required)
NUMBER AND SIZE	7 or 11 blade cutting head units, 46 cuts per metre at 7.5mph (12km/h)
ROLLERS	Front: Full width 3" (75mm) diameter grooved roller · Rear: Full width 3" (75mm) diameter plain roller
ADJUSTMENT	Self-locking hand adjusters
CUTTING UNIT LIFT	Wing units can be raised individually for transport

TRACTION, BRAKES & SPEED

TRACTION DRIVE	SureTrac™ Traction System with full-time four wheel drive in forward and reverse, parallel cross series system for excellent grip and a light touch
CUTTING UNIT DRIVE	Fixed displacement hydraulic motors directly coupled to cutting unit
HYDRAULIC SYSTEM	8.31 gal (37.8L) capacity; Grade of oil to A.P.I. Classification CE/SF grades SAE 10W-30
SERVICE BRAKES	Hydrostatic braking
PARKING BRAKES	Zero-maintenance wet parking brakes
STEERING	Hydrostatic power steering with adjustable tilt steering wheel
MOWING SPEED	Selectable up to 7.5mph (12km/h)
TRANSPORT SPEED	Selectable up to 8.7mph (14km/h)
REVERSE SPEED	Selectable up to 4mph (6.4km/h)

WEIGHTS & DIMENSIONS

WEIGHT (excluding fuel)	3450lbs (1565Kg)
WEIGHT TRANSFER	Hydraulically adjustable weight transfer to boost traction
LENGTH	116" (2.95m)
OVERALL HEIGHT	85" (2.15m)
WHEELBASE	65" (1.65m)
TRANSPORT WIDTH	99.2" (2.52m)
WORKING WIDTH	130" (3.31m)

WARRANTY

MOWER WARRANTY	2 Years
----------------	---------

ACCESSORIES

- 26" (66cm) powered rear cleaning brush
- Grass catchers
- Grammer air suspension seat
- LED working light kit
- Sun canopy