



Sand Star E

Do More with Electric

The Sand Star E is the groomer of choice for golf course superintendents who are searching for an energy-efficient solution for smooth bunkers. With superior traction and stability, the Sand Star E is built to last. Equipped with a 48V lithium ion battery, the Sand Star E delivers peak performance for up to 8 hours.

With over 25 accessories and industrial-grade components, the Sand Star E is adaptable to the unique needs of your course. As one of the latest addition to Smithco's star lineup of groomers, the Sand Star E is one you are going to love adding to your fleet.

• BATTERY

The Sand Star E incorporates the Roy-Pow 150 amp lithium battery pack, with an onboard battery management system, supported by a five-year, non-prorated manufacturer's warranty.

• ONBOARD DIAGNOSTICS

The Sand Star E's onboard diagnostic system allows you to quickly and easily identify solutions in various subsystems - saving you time and money.

• DUAL-PEDAL TRACTION

The Sand Star E's exclusive dual-pedal traction gives the operator the ability to smoothly transition from forward to reverse, making for hands-free operation and allowing the operator the ability to focus on steering and plowing.

• MOTOR

The Sand Star E is an engineered electric bunker rake utilizing state-of-the-art, industrial-grade motor and controller technology, while delivering superior and reliable power for even the toughest jobs.

Exceptional Service and Products Since 1967
smithco.com

Smithco
WE TAKE YOUR TURF SERIOUSLY

Sand Star E

SPECIFICATIONS

Smithco

United States | 877.833.7648
International | +1 610.688.4009

BATTERY

Type	Roy Pow 48V 150 Ah lithium battery pack 5-year, non-prorated warranty
Nominal Voltage	51V
Stored Energy (Wh/kg)	8.2 kWh
Dimension (LxWxH)	31.5 x 14.25 x 8.75 in (80 x 36 x 22.1 cm)
Weight	159 lbs (72 kg)

TRACTION DRIVE

Traction System	Dana transaxel, two wheel drive, forward/reverse drive pedals at operator's station
-----------------	---

ENGINE

Type	Mahle
Rated Horsepower	6 hp (4.47 kw)
Displacement	48 v; continuous AC induction
Current	Sevcon Gen 4, Size 4, 450A 2min 540A Boost
Peak Torque	83 nm

TIRES, BRAKES & STEERING

Service Brakes	Dynamic braking through electrical regen system
Tires	Front 20x10-turf10 tires; Rear 25x10-turf12 tires
Parking Brake	Push button
Steering	Manual chain drive front wheel steering

PRODUCT CONFIGURATION

Description	3-wheel tricycle design
Pedal	Dual foot pedal for forward and reverse operation
Levers	Electric engage/disengage switches for rear mounted and center mounted attachments

SPEED & SOUND

Reverse	0-5 mph (0-8 kph)
Forward	0-10 mph (0-16 kph)
Sound Level	0 dba

WEIGHTS & DIMENSIONS

Ground Clearance	5.5-7 in (13-18 cm) under cultivator, depending on attachment
Height	52 in (1.3 m)
Width	58 in (1.5 m)
Length	68 in (1.7 m)
Weight	735 lbs (333 kg) with batteries

revised 1/2024

Learn More Today!

