

Sand Star

The Sand Star I stands as the preferred groomer for grounds crews seeking exceptional traction, enhanced stability, and an extensive array of implements. Crafted with industrial-grade materials, the Sand Star I is designed for long-lasting performance at your facility. With a versatile selection of over 50 accessories and industrial-grade components, the Sand Star I can be customized to suit the distinctive requirements of your field.

PERFORMANCE

Optimal raking and progressive throttling is achieved with the "Speed Boss" Speed Control System. Spend less time fixing mistakes and more time enjoying your field.

PRODUCTIVITY

Center and rear implements, plows, key switches, and other controls are located conveniently in the operator position, which has been ergonomically designed for safety, comfort, and productivity. With the Sand Star I, you never have to leave the machine.

• OPTIONS

With over 50 accessories and industrial-grade components, Smithco's groomers are built to last as your course changes and grows.

INTERCHANGEABILITY

Smithco's Sand Star's are equipped with a single point quick hitch for easy interchangeabiilty of implements and attachments. You spend less time manuevering equipment and more time getting the job done.

Exceptional Service and Products Since 1967 smithco.com



Sand Star I SPECIFICATIONS

Smithco United States | 877.833.7648 International | +1 610.688.4009

ENGINE	The state of the state of the	
Туре	Vanguard V-twin air cooled	
Displacement	29.3 in³ (480 cc)	
Rated Horsepower	16 hp (11.9 kW)	
Air Cleaner	Engine mount and remote cyclonic	
Cooling	Air-cooled	
Lubrication	Full pressurized	
Oil Filter	Full flow; Spin on type	
Electrical System	16 amp, with 12V 300 CCA battery, fuse protected	
Fuel Capacity	5 gal (18.9 l)	

TRACTION DRIVE

Traction System	Variable displacement hydraulic pump; Individual hydraulic wheel motors on rear
Hydraulic System	5 gal (18.9 l)
Hydraulic Cooling	Full flow filter with oil cooler
A	

TIRES, BRAKES & STEERING

Tires	22–11 x 10.0 Knobby Tire
Service Brakes	Hydrostatic
Parking Brake	Hand operated, 8 in (20 cm) disk type
Steering	Manual chain drive front wheel steering

SPEED

Transport	0-12 mph (0-19.3 kph)
Reverse	0–5 mph (0–8 kph)

WEIGHTS & DIMENSIONS

	· · ·
Weight	875 lbs (397 kg)
Length	68 in (v 1.7 m)
Width	58 in (1.5 m)
Height	52 in (1.3 m)
Ground Clearance	5.5-7 in (13-18 cm)
Wheelbase	68 in (1.7 m)

