

# ***Tournament Ultra XL 70***



## ***More Productive Turf Rolling***

The Tournament Ultra XL 70 Greensroller is engineered for maximum productivity and efficiency on turf. Featuring three articulating rolling heads, this turf roller offers a generous 70" wide rolling area, dramatically reducing rolling time. Its direct drive to rollers eliminates time-consuming chain maintenance, ensuring easy upkeep.

Equipped with a powerful 16 hp Briggs Vanguard gasoline engine, the Tournament Ultra XL 70 boasts a hydraulic drive system with triple hydraulic direct drive to rollers for superior traction. The hydrostatic drive allows for an infinitely variable speed range of 0-7 mph, enhancing control during operation.

### **• EFFICIENT ROLLING**

The Tournament Ultra XL 70's three articulating rolling heads cover a wide 70" area, significantly reducing rolling time and enhancing productivity on turf.

### **• LOW MAINTENANCE**

With direct drive to rollers and a hydraulic system, this turf roller eliminates time-consuming chain maintenance, ensuring easy upkeep for course managers.

### **• SUPERIOR TRACTION**

Triple hydraulic direct drive to rollers provides exceptional traction, making the Tournament Ultra XL 70 effective on diverse turf and terrain conditions for a safe and efficient operation.

### **• POWERFUL PERFORMANCE**

Featuring a robust 16 hp Briggs Vanguard engine and hydrostatic drive, this turf roller offers variable speeds up to 7 mph, giving operators precise control and efficiency during course maintenance.

**Exceptional Service and Products Since 1967**  
**smithco.com**

***Smithco***  
**WE TAKE YOUR TURF SERIOUSLY**

# Tournament Ultra XL 70

## SPECIFICATIONS

# Smithco

United States | 877.833.7648  
International | +1 610.688.4009

### ENGINE

Type	Briggs Vanguard gasoline engine
Cooling	Air cooled
Lubrication	Full pressurized
Rated Horsepower	16 hp (11.9 kw)
Drive System	Hydrostatic using a 1 in <sup>3</sup> (16 cc) hydraulic pump driving three hydraulic motors direct coupled to each roller cylinder; Direct drive motors eliminate maintenance, hydraulic drive to all rollers provides superior traction in all turf and terrain conditions
Battery	12 v
Liquid Capacity	5 gal (18.9 l) hydraulic oil tank
Air Cleaner	Engine mounted
Fuel Capacity	5 gal (18.9 l) gas tank
Ignition	Electronic

### PRODUCT CONFIGURATION

Configuration	A gasoline engine powered, hydraulic drive, riding turf roller; Hydraulic, triple roller drive system for superior traction and safety; Direct drive hydraulic motors to each roller cylinder eliminating the maintenance required on mechanical drive systems
Seat	High back, one piece for operator comfort
Safety	Triple drive roller system for superior traction and safe operation in all turf and terrain conditions; Dynamic braking thru hydrostat drive system

### ROLLERS

Construction	Heavy gauge square steel tubing main frame, hydraulically formed, electrically welded
Rollers	(2) 8 in (20.3 cm) diameter x 19 in (48.3 cm) length and (1) 8 in (20.3 cm) diameter x 36 in (91.4 cm) seamless drawn over mandrel steel tubes; Beveled on both ends with roller scrapers; Bolted hubs with bearings on each end of both rollers
Controls	Keyed ignition switch, engine throttle, choke at the operator's station; Dual drive pedals control left / right operation and rolling speed; Pedals connected to hydraulic pump via fully sealed push / pull cable system
Ground Pressure	3.8 psi (0.3 bar)
Electrical System	12 v, electric start to engine

### TRANSPORT TRAILER

Description	Low profile design with drop axle; Extra wide metal bed and tailgate fitted with rubber matting for traction and centering guide system for easy load/unload of the roller
Width	2500 lbs (1134 kg)
Capacity	56 in (1.4 m)
Length	47 in (1.2 m) (tailgate up, not including drawbar)
Weight	240 lbs (528 kg)
Drawbar	Adjustable from 44-47 in (1.1-1.2 m)
Tires	18-9.5x8 pneumatic

### TIRES, BRAKES & STEERING

Braking	Dynamic through hydrostatic drive system
Steering	10:2 reduction; 16 in (40.6 cm) soft grip steering wheel with tilt; 10 in (25.4 cm) diameter turning radius; Hydraulic power steering

### WARRANTY

Warranty	Smithco two (2) year limited warranty Briggs & Stratton two (2) year engine manufacturer warranty
----------	---

### WEIGHTS & DIMENSIONS

Weight	905 lbs (410.5 kg)
Length	48 in (1.2 m)
Width	73 in (1.9 m)
Height	47 in (1.2 m)

### SPEED & SOUND

Transport	0-10 mph (0-16 kph)
Speed	0-9 mph (0-14.5 kph)
Sound Level	72 dBA



Learn More Today!